

Manufacturers of High Security Vaults & Safety Lockers









Model: STRONG ROOM DOOR-CLASS I (INNER OPENING)



TECHNICAL SPECIFICATIONS

: Height 84" X Width 48"(7' ht x 4' wt) Class Type : Class - C (TRTL 15 - FR 30) Frame Dimensions

Door Dimensions : Height 72" X Width 36"(6' ht x 3' wt) Classification : Fire, Drill, Tools, Torch & Blast Resistant

Door Opening : Inner Opening Wall Construction : Reinforced Harden Material

Opening Type : Right / Left Hinges Anti-Burglary System : Anti-Theft Technology with Dead Lock System

Locking Systems : All the 4 Sides Locks : 2 Locks with Interlocking Single Door

Front Barrier Slab : 75 mm (3 inches) : UL Listed Double Bitted Keys (A1, B1, 2) Keys

: Door Construction with Triple Wall Layers **Total Door Thickness** : 175mm (7 Inches) Construction

Shooting Bolt Thickness: 40 mm Diameter Finish : Poly Acrylic Urethane Finish

No. of Shooting Bolts Total Weight : 1000 Kgs (Without Packing) : 16 No's

*Optional: Customized dimensions also available

LOCK OPTIONS



Electronic Encoded Lock



Biometric - Fingerprint Lock



Mechanical Combination Lock

*Dimensions and weights are subject to variations of \pm 5%-10% during manufacturing



No.64, F-2, 1st Floor, Audilok Jayalakshmi, Sree Sayee Nagar Annexe, 3rd Cross Street, Virugambakkam, Chennai- 600 092.

FIRE RESISTANT

Manufacturing Unit / Office: No.16, Vignesh Industrial Estate, Indunagar, Chinnavedampatti, Coimbatore - 641 049.

FOUR WAY SHOOTING BOLTS

Email: shelterssaffin@gmail.com Website: www.shelterssaffin.com www.sheltersecuritysystems.com

DOUBLE BITTED

TRIPLE WALL

 Tough Steel Plates & Armor Plates
Oxyacetylene Flame Resisting Material
Special Fire & Hammer Resisting Material
Highly Secured Dual Control Key Locks
With S Charles Dualisted Contact / WhatsApp: 99443 65493 95974 14141 0422 2666535

MATERIAL OF UNIQUE CONSTRUCTION

Chennai Outlet / Office:

Other Branches: Pondicherry, Vellore, Krishnagiri & Ramanathapuram.