

Manufacturers of High Security Vaults & Safety Lockers









## Model: STRONG ROOM DOOR-CLASS II (OUTER OPENING)





## **TECHNICAL SPECIFICATIONS**

: Height 84" X Width 48"(7' ht x 4' wt) Frame Dimensions Class Type : Class - B (TRTL 30 - FR 30)

**Door Dimensions** : Height 72" X Width 36"(6' ht x 3' wt) Classification : Fire, Drill, Tools, Torch & Blast Resistant

**Door Opening** : Outer Opening Wall Construction : Reinforced Harden Material

Opening Type : Right / Left Hinges Anti-Burglary System : Anti-Theft Technology with Dead Lock System

**Locking Systems** : All the 4 Sides Locks : 2 Locks with Interlocking Single Door

Front Barrier Slab : 100 mm (4 inches) : UL Listed Double Bitted Keys (A1, B1, 2) Keys

: Door Construction with Triple Wall Layers **Total Door Thickness** : 200mm (8 Inches) Construction

Finish : Poly Acrylic Urethane Finish Shooting Bolt Thickness: 40 mm Diameter

No. of Shooting Bolts : 16 No's **Total Weight** : 1250 Kgs (Without Packing)

\*Optional: Customized dimensions also available

## **LOCK OPTIONS**



Electronic Encoded Lock



Biometric - Fingerprint Lock



TRIPLE WALL CONSTRUCTION

Mechanical Combination Lock

\*Dimensions and weights are subject to variations of  $\pm$  5%-10% during manufacturing



No.64, F-2, 1st Floor, Audilok Jayalakshmi, Sree Sayee Nagar Annexe, 3<sup>rd</sup> Cross Street, Virugambakkam, Chennai- 600 092.

FIRE RESISTANT

Manufacturing Unit / Office: No.16, Vignesh Industrial Estate, Indunagar, Chinnavedampatti, Coimbatore - 641 049.

FOUR WAY SHOOTING BOLTS

Email: shelterssaffin@gmail.com Website: www.shelterssaffin.com www.sheltersecuritysystems.com

 Tough Steel Plates & Armor Plates
Oxyacetylene Flame Resisting Material
Special Fire & Hammer Resisting Material
Highly Secured Dual Control Key Locks
with 5.5 Keys In Duplicate Contact / WhatsApp: 99443 65493 95974 14141

0422 2666535

MATERIAL OF UNIQUE CONSTRUCTION

Chennai Outlet / Office:

Other Branches: Pondicherry, Vellore, Krishnagiri & Ramanathapuram.